

relative to the cart and] to isolate the contents thereof.--

In the claims:

Claims 2, 3, and 9 have been cancelled without prejudice.

New claims 21 through 24 have been submitted with this Amendment.

The following claims have been amended:

1. (Amended) A cover assembly for a cart, said cover assembly comprising:
 - a) an enclosure including a hollow interior dimensioned to receive the cart therein when said enclosure is disposed in an operative position,
 - b) said enclosure including a top and a sidewall, said top disposed in overlying relation to an upper portion of the cart and said sidewall depending downwardly from said top in overlying, at least partially surrounding relation to a plurality of sides of the cart,
 - c) an access opening formed in said sidewall in aligned relation with a corresponding side of the cart,
 - d) a closure structure selectively positionable between a closed and an open position relative to said access opening, [and]
 - e) said access opening disposed and dimensioned to access contents of the cart and allow passage of the contents therethrough, when said closure is in said open

position[.]_

- f) said enclosure formed of a flexible, hypo-allergenic material selectively oriented in either said operative position or a collapsed stored position, and
 - g) a storage assembly including at least a first compartment mounted within said hollow interior of said enclosure, said first compartment disposed and structured to isolate the contents thereof from the cart and a remainder of said hollow interior of said enclosure.
4. (Amended) A cover assembly as recited in claim 1 wherein said access opening is [dimensioned and] disposed in overlying alignment with at least a majority of one side of the cart.
7. (Amended) A cover assembly as recited in claim 6 wherein said drape is correspondingly dimensioned and configured to said access opening and disposed in overlying, covering relation to the one side of the cart when said closure structure is in said closed position.
10. (Amended) A cover assembly as recited in claim [9] 1 wherein said storage assembly further comprises at least a second compartment secured to an exterior of said wall assembly and structured to removably contain contents removed from said cart.
11. (Amended) A cover assembly as recited in claim 10 wherein said storage assembly further comprises at least a third

compartment secured to an exterior of said enclosure and including a window formed therein, said window disposed in aligned relation with an interior of said third compartment to facilitate viewing of the interior of said third compartment there through.

20. (Amended) A cover assembly designed to be removably mounted on a mobile cart, said cover assembly comprising:
- a) an enclosure including a hollow interior dimensioned to receive a cart therein when said enclosure is oriented in an operative position,
 - b) said enclosure including a top and a sidewall, said top disposed in overlying relation to an upper portion of said cart and said sidewall extending downwardly from said top in overlying, at least partially surrounding relation to a plurality of sides of the cart,
 - c) an access opening formed in said sidewall in aligned relation with a corresponding portion of the cart,
 - d) a closure structure selectively positionable between a closed position and an open[ed] position[ed] relative to said access opening,
 - e) said access opening disposed and dimensioned to access contents of the cart and allow passage of the contents therethrough when said closure is in said open position[ed],
 - f) said enclosure including an open bottom disposed at a

lower end of said sidewall and dimensioned to allow a bottom of the cart to pass therethrough,

- g) a reinforcement assembly comprising a plurality of reinforced portions connected to said enclosure at a plurality of spaced apart locations, [at least some of] [said plurality of reinforced portions in extending] [outwardly from an exterior surface of said enclosure, and]
- h) said plurality of reinforced portions comprising a plurality of corner pads disposed in overlying, at least partially covering relation to corner portions of the upper portion of the cart,
- i) said reinforcement portions further comprising an elongated peripheral seam extending continuously along an exterior of said enclosure contiguous to a commonly exposed peripheral junction between said side wall and said top, and
- j) a storage assembly including at least one pocket mounted on an interior of said sidewall and structured to isolate the contents thereof from said cart when said enclosure is in said operative position.